

AJ5800 型电脑输液泵

AJ5800 VOLUMETRIC INFUSION PUMP

产品主要技术指标

- 工作环境温度: 5℃-40℃
- 工作电源交直流两用: AC 220V (AC110V)50Hz 或 DC 12V
- 功耗不大于: 40VA
- 输入容量计数: 0-9999ml
- 流量设定范围: 1-1000ml/hr, 最小增加量 1ml/hr
- 用量限制范围: 1-9999ml/hr
- 输液准确度: 1-1000ml/hr \pm 10%
- 有“完成”,“阻塞”,“气泡”,“开门”及“电池欠压”声光报警功能
- 在“完成”或“气泡”报警时, 产品有静脉开放(KVO)速度, KVO 速度为 1-2ml/hr
- 机内电池自动切换, 完全充电后在 50ml/hr 流量时可连续使用 4 小时以上
- 体积(L \times B \times H): 190 \times 125 \times 250mm
- 重量: 4.25kg

- Ambient Temperature: 5 °C - 40 °C
- Power Supply: AC 220V 50Hz or DC 12V(AC110V available if required)
- Power Consumption: less than 40VA
- Infused Volume Range: 0 - 9999ml
- Flow Rate Range: 1 - 1000ml/hr in 1ml/hr increments
- Infusion Limitation Options: 1 - 9999ml/hr
- Infusion Accuracy: 1-1000ml/hr \pm 10%
- Audible and Visual Alarms of "COMPLETE", "OCCLUSION", "AIR-IN-LINE", "DOOR OPEN" and "LOW BATT"
- Keep vein open(KVO)rate will be activated once "COMPLETE" or "AIR-IN-LINE" alarms
- 4 hours continuously operation at 50ml/hr with built-in rechargeable Ni-MH battery
- Dimension (L \times B \times H): 190 \times 125 \times 250mm
- Weight: 4.25kg

