

PALCO  
OXIMETER  
MODEL

# 300

- Fits into lab coat pocket—convenient for spot checks.
- Over 1,000 readings on one set of 6 "AA" alkaline batteries.
- NiCad rechargeable version also available.
- Bright LED displays for saturation and pulse rate.
- Rugged, water-resistant case withstands shock and vibration.

**Optional Hip Carry Case**  
Conveniently carries the Model 300 series at belt-level. Helps to prevent misplacing the oximeter in a busy hospital setting.



## MODEL 300 SPECIFICATIONS

<b>Oxygen Saturation and Pulse Rate</b>	Display	Two 3-digit, 7-segment LED 1.1cm (0.4 in) high characters
	Resolution	1% SpO <sub>2</sub> or 1 beat/minute (BPM)
	Range	SpO <sub>2</sub> : 0–100% Pulse: 25–250 BPM
	Accuracy	SpO <sub>2</sub> : 100–70%, ±2% 69–60%, ±3% Less than 60% unspecified Pulse: 25–250 BPM, ±2
<b>General</b>	Size	19.05cm L × 8.89cm W × 3.5cm H (7½ in L × 3½ in W × 1⅜ in H)
	Weight	460 gms (1.01 Lbs) with batteries
<b>Sensor Compatibility</b>	Uses all Palco Opto-Plethysmographic Sensors	
<b>Power Source</b>	Battery Type	6 "AA" Alkaline batteries or NiCad rechargeable version
	Battery Life in continuous operation	"AA" Alkaline version—8 hours NiCad version—12 hours
	Adaptor for rechargeable version	120V, 60Hz AC to 12V DC, or 230V, 50Hz AC to 12V DC

